



DIN	p		b ₁ min. [mm]	b ₂ max. [mm]	b ₃ min. [mm]	d ₁ max. [mm]	d ₂ max. [mm]	d ₃ min. [mm]	e [mm]	g max. [mm]	K ₁ max. [mm]	L ₁ max. [mm]	Bruchkraft min. [N]	Gewicht ca. kg/m	
	[mm]	[inch]													
04C-1	25	6,35	1/4"	3,18	4,80	4,85	3,30	2,31	2,34	-	6,00	2,5	6,6	3.500	0,13
06C-1	35	9,525	3/8"	4,68	7,47	7,52	5,08	3,28	3,63	-	9,10	3,3	9,9	7.900	0,35
08A-1	40	12,70	1/2"	7,85	11,15	11,28	7,95	3,96	4,01	-	12,00	3,9	17,8	14.100	0,60
10A-1	50	15,875	5/8"	9,40	13,80	13,93	10,16	5,08	5,13	-	15,00	4,1	21,8	22.200	1,00
12A-1	60	19,05	3/4"	12,57	17,70	17,85	11,91	5,94	5,99	-	18,00	4,6	26,9	31.800	1,50
16A-1	80	25,40	1"	15,75	22,50	22,70	15,88	7,92	7,96	-	24,10	5,4	33,5	56.700	2,60
20A-1	100	31,75	1 1/4"	18,90	27,40	27,60	19,05	9,53	9,59	-	30,10	8,1	41,1	88.500	3,70
24A-1	120	38,10	1 1/2"	25,22	35,30	35,60	22,23	11,10	11,17	-	36,20	6,6	50,8	127.000	5,50
28A-1	140	44,45	1 3/4"	25,22	37,00	37,30	25,40	12,70	12,77	-	42,20	7,4	54,9	172.400	7,50
32A-1	160	50,80	2	31,55	45,00	45,30	28,58	14,27	14,35	-	48,20	7,9	65,5	226.800	9,70
40A-1	200	63,50	2 1/2"	37,85	54,70	55,00	39,68	19,84	19,92	-	60,30	10,0	80,3	353.800	15,80
48A-1	240	76,20	3"	47,35	67,50	68,00	47,63	23,80	23,90	-	73,20	10,0	95,5	510.300	22,60