



DIN	p		b ₁ min. [mm]	b ₂ max. [mm]	b ₃ min. [mm]	d ₁ max. [mm]	d ₂ max. [mm]	d ₃ min. [mm]	e [mm]	g max. [mm]	K ₁ max. [mm]	L ₁ max. [mm]	Bruchkraft min. [N]	Gewicht ca. kg/m	
	[mm]	[inch]													
04C-3	25	6,350	1/4"	3,18	4,80	4,85	3,30	2,31	2,34	6,40	6,00	2,5	6,6	10.500	-
06C-3	35-3	9,525	3/8"	4,68	7,47	7,52	5,08	3,28	3,63	10,13	9,10	3,3	9,9	23.700	1,1
08A-3	40-3	12,700	1/2"	7,85	11,15	11,28	7,95	3,96	4,01	14,38	12,00	3,9	17,8	42.300	1,8
10A-3	50-3	15,875	5/8"	9,40	13,80	13,93	10,16	5,08	5,13	18,11	15,00	4,1	21,8	66.600	2,9
12A-3	60-3	19,050	3/4"	12,57	17,70	17,85	11,91	5,94	5,99	22,78	18,00	18,4	4,6	95.400	4,3
16A-3	80-3	25,400	1"	15,75	22,50	22,70	15,88	7,92	7,96	29,29	24,10	5,4	33,5	170.100	7,5
20A-3	100-3	31,750	1 1/4"	18,90	27,40	27,60	19,05	9,53	9,59	35,67	30,10	8,1	41,1	265.500	11,0
24A-3	120-3	38,100	1 1/2"	25,22	35,30	35,60	22,23	11,10	11,17	45,44	36,20	6,6	50,8	381.000	16,5
28A-3	140-3	44,450	1 3/4"	25,22	37,00	37,30	25,40	12,70	12,77	48,87	42,20	7,4	54,9	517.200	21,7
32A-3	160-3	50,800	2	31,55	45,00	45,30	28,58	14,27	14,35	58,55	48,20	7,9	65,5	680.400	28,3
40A-3	200-3	63,500	2 1/2"	37,85	54,70	55,00	39,68	19,84	19,92	71,55	60,30	10,0	80,3	1.061.400	48
48A-3	240-3	76,200	3"	47,35	67,50	68,00	47,63	23,80	23,90	87,83	73,20	10,0	95,5	1.530.900	66